



Easily connect THREADs to your existing network using the following simple steps:

1 POWER ON

Plug DC Power into the power port.

 LED Connected

THREAD is powered on and is connected to the internet

3 SEC. BETWEEN GREEN PULSE 

 LED Disconnected

THREAD is powered on but is not able to reach the internet

3 SEC. BETWEEN RED PULSES 

2 CONNECT TO INTERNET

Connect THREAD directly to your network by plugging the ethernet cable to the 'Network' port found on the front of the THREAD. DHCP services must be available on the network.

Note: Any THREAD connected directly to the network will assume the role of a 'Gateway' for wireless access point for other THREADs in the vicinity.

3 WIRELESS CONNECTIONS

THREADs not connected by network cable can wirelessly connect to any existing Gateway. Attach antennas when wireless communication is required.

4 LOGIN TO **sensemetrics**

Cloud application:

<https://app.sensemetrics.com>

New users can register for an account here:

<https://app.sensemetrics.com/#register>

5 ADD CONNECTION

Navigate to CONFIGURE > CONNECTIONS > ADD CONNECTION

Select THREAD from the drop down menu and enter your Connect Code:

 Unique 6-digit code on the back of each THREAD



DB0X12

6 ADD DEVICE

Navigate to CONFIGURE > DEVICES > ADD DEVICE

Connect and configure up to two sensemetrics supported Devices to your THREAD

 Visit the sensemetrics support Help Center for additional information: www.support.sensemetrics.com